



Higher Land Ratio Pattern Design offers Maximum Ground Contact Surface



Special Developed Super-Lasting Tread Compound Brings Excellent Service Life



E Series **Kilomax**

- ◆ Higher Land Ratio Surface gives longer service life
- ◆ Best cost & performance combination
- ◆ Environmental Friendly



Kilomax



Kilomax is the ultimate workhorse because it is designed to run exceedingly well in virtually all applications. Kilomax utilizes natural rubber in a 4-stage construction. Because Kilomax has braided wire in the bead area; it will not spin on the wheel. Fleet manager's will benefit from a tire that provides high performance without having to sacrifice operator comfort.

TYRE SIZE	STANDARD RIM	Heel Tyre		Dimensions (inch)		Load Capacity(lbs)					
		Quick	Standard	Section Width	Overall Diameter +/-2%	Forklift		Other Vehicles			Static (0 km/h)
						Load Wheel 25km/h	Steer Wheel 25km/h	6km/h	10km/h	25km/h	
4.00-8	2.50C-8	<input type="checkbox"/>	<input type="checkbox"/>	4.7	16.1	2094	1609	2094	1896	1609	2425
	3.00D-8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>								
	3.25I-8	<input type="checkbox"/>	<input type="checkbox"/>								
	3.75-8	<input type="checkbox"/>	<input type="checkbox"/>								
5.00-8	3.00D-8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	5.1	18.1	3120	2403	3120	2833	2403	3627
	3.50D-8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	5.4							
15x4 1/2-8(125/75-8)	3.00D-8	<input type="checkbox"/>	<input type="checkbox"/>	4.6	15.0	2293	1764	2293	2072	1764	2668
16x6-8(150/75-8)	4.33R-8	<input type="checkbox"/>	<input type="checkbox"/>	6.1	16.4	3296	2535	3296	2987	2535	3825
18x7-8(180/70-8)△	4.33R-8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	6.0	18.0	4729	3638	4729	4288	3638	5489
140/55-9	4.00E-9	<input type="checkbox"/>	<input type="checkbox"/>	5.3	15.1	2579	1984	2579	2337	1984	2998
6.00-9	4.00E-9	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	6.1	20.8	4156	3197	4156	3770	3197	4828
	6.00E-9	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7.5	20.9	6074	4674	6074	5523	4674	7055
21x8-9(200/75-9)	7.00E-9	<input type="checkbox"/>	<input type="checkbox"/>			6382	4905	6382	5787	4905	7407
	5.00F-10	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	6.5	22.8	5159	3968	5159	4685	3968	5997
23x9-10(225/75-10)	6.50F-10	<input type="checkbox"/>	<input type="checkbox"/>	8.0	23.3	7595	5842	7595	6889	5842	8818
200/50-10	6.50F-10	<input type="checkbox"/>	<input type="checkbox"/>	7.8	18.2	5445	4189	5445	4938	4189	6327
7.00-12	5.00S-12	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	6.9	25.9	6437	4938	6437	5831	4938	7452
	6.50-12	<input type="checkbox"/>	<input type="checkbox"/>	9.6		7385	5677	7385	6702	5677	8576
27x10-12(250/75-12)	8.00G-12	<input type="checkbox"/>	<input type="checkbox"/>	9.8	27.2	8598	6614	8598	7804	6614	9987
7.00-15	5.50-15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7.2	28.9	7815	6008	7815	7088	6008	9072
	6.00-15	<input type="checkbox"/>	<input type="checkbox"/>								
8.25-15	6.50-15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	8.5	32.6	10141	7804	10141	9204	7804	11784
	6.50-15	<input type="checkbox"/>	<input type="checkbox"/>								
28x9-15(8.15-15)225/75-15	7.00-15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	8.8	27.4	8311	6393	8311	7540	6393	9656
	7.00-15	<input type="checkbox"/>	<input type="checkbox"/>	9.0	28.7	10461	8047	10461	9259	8047	12147
250-15(250/70-15)	7.50-15	<input type="checkbox"/>	<input type="checkbox"/>	9.1							
	8.00-15	<input type="checkbox"/>	<input type="checkbox"/>	10.2	32.7	12897	9921	12897	11706	9921	14980
7.50-16	5.50-16	<input type="checkbox"/>	<input type="checkbox"/>	8.3	31.1	8741	6724	8741	7937	6724	10152
	6.00-16	<input type="checkbox"/>	<input type="checkbox"/>								
9.00-16	5.50-16	<input type="checkbox"/>	<input type="checkbox"/>	8.5	33.1	9601	7385	9601	8719	7385	11155
	6.00-16	<input type="checkbox"/>	<input type="checkbox"/>								
7.50-20	6.00-20	<input type="checkbox"/>	<input type="checkbox"/>	8.8	34.7	8598	7165	8598	7881	7165	10825
	6.50-20	<input type="checkbox"/>	<input type="checkbox"/>								
8.25-20	6.50-20	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			9700	8047	9700	8774	8047	12147
	7.00-20	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	8.8	38.8	10141	8543	10141	9314	8543	12897
	7.50-20	<input type="checkbox"/>	<input type="checkbox"/>								
9.00-20	6.50-20	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>								
	7.00-20	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	8.9	38.9	11905	9921	11905	10814	9921	14980
	7.50-20	<input type="checkbox"/>	<input type="checkbox"/>								

△ The rim contour may vary from different vehicle manufacturers, please contact with EXMILE technical department for details.

◆ Available

□ Under Development