



# ARMADILLO TIRE SOLUTION

INDUSTRIAL INDUSTRIAL INDUSTRIAL INDUSTRIAL INDUSTRIAL

Tire Life




Stability



Armadillo Tire Solution

Solid footprint for superior traction & stability



The Armadillo Tire Solution line of Premium Solids has an outstanding lifetime due to the innovative tread design and special compounds.

The large contact area and innovative tread design reduce tire stress and uneven wear for maximum performance and tire lifetime.



Improved traction and performance through non directional tread design.

Non-marking

3 Stage technology for premium quality rubber tread/cushion/frcc base/steel.



Tire Size	Rim Size	Outside Diameter	Static Radius Under Load	Section Width	Approx. Net Weight	Load Capacity (kg)			Other Industrial Vehicles
						Counter Balanced Lift Trucks			
* Under Development		(mm)	(mm)	± 5 mm	± 1.5% (kg)	10 km/h Driving/Steering	16 km/h Driving/Steering	25 km/h Driving/Steering	16 km/h
5.00-8	3.00D.3.50D	469	221	127	18.5	1210/970	1175/880	1095/820	840
* 15 x 4.5-8	3.00D.3.25	380	179	106	10.0	905/725	875/655	805/605	625
* 16x6-8	4.33R	418	197	156	16.8	1500/1200	1445/1085	1345/1010	1035
18x7-8	4.33R	457	214	154	20.7	2350/1880	2265/1700	2110/1585	1620
6.00-9	4.00E	545	256	148	28.0	1920/1535	1855/1390	1730/1295	1325
* 21x8-9	6.00E	535	250	189	35.0	2810/2250	2715/2035	2530/1895	1940
6.50-10	5.00F	597	281	158	37.5	2640/2110	2545/1910	2370/1780	1820
* 200 / 50-10	6.50F	458	211	198	25.3	2370/1900	2290/1720	2135/1605	1630
* 23x9-10	6.50F	595	279	211	52.0	3420/2735	3300/2475	3075/2305	2355
7.00-12	5.00S	683	322	167	48.0	3015/2410	2910/2185	2710/2035	2075
* 23 x 10-12	8.00G	597	282	230	52.0	4005/3205	3845/2885	3605/2705	2765
* 27x10-12	8.00G	683	320	236	73.0	4465/3570	4315/3235	4020/3015	3080
7.00-15	5.50S.6.00	759	360	186	64.5	3590/2870	3465/2600	3225/2420	2475
8.25-15	6.50T. 5.50S	847	400	212	97.0	4940/3950	4765/3575	4440/3330	3405
28 x 9-15	7.00	706	335	230	69.0	4090/3270	3945/2960	3675/2755	2820
250-15	7.00. 7.50	735	348	235	77.5	4365/3490	4220/3160	3930/2955	3010
300-15	8.00	838	384	256	115.5	5990/4790	5780/4335	5380/4035	4130
* 355/65-15	9.75	823	384	301	134.0	7120/5700	6880/5170	6410/4820	4910
* 9.00-16	6.50	884	418	218	109.5	5135/4110	4965/3725	4625/3470	3550
* 8.25-20	6.50T. 7.00	992	472	219	130.2	2425/4340	5240/3930	4880/3735	3475
* 9.00-20	6.50T-7.00	1038	471	238	151.8	6450/5160	6235/4675	5805/4355	4450
10.00-20	7.50-8.00	1073	508	252	175.0	7240/5795	6995/5245	6510/4885	4995
* 11.00-20	7.50-8.00	1058	502	277	195.0	7560/6050	7300/5490	6810/5120	5210
12.00-20	8.00-8.50	1146	528	290	235.0	8445/6755	8105/6080	7600/5700	5825
* 14.00-20	10.00	1260	590	332	363.0	10800/8640	10430/7840	9730/7315	7450
* 12.00-24	8.50	1247	591	309	287.0	9575/7655	9235/6925	8600/6450	6595
* 14.00-24	10.00	1368	636	335	391.0	11865/9490	11390/8545	10680/8010	8185



WWW.ARMADILLOTIRE.COM

(855)860-5618 SALES@ARMADILLOTIRE.COM