



MILEMAX

◆ Agressive Unique Pattern Design ◆ Extra Deep Lug

Armadillo Tire LLC

WWW.ARMADILLOTIRE.COM Toll free : (855)860-5618
317 South McLennan Loop Elm Mott, TX 76640

MILEMAX

MILEMAX branded Pneumatic Shaped Solid tires are a three stage tire with braided wire in the bead area which are designed to provide for a cooler running, longer lasting tire which will not spin on the wheel. Your customers will immediately notice the unique tread pattern and tread depth. MILEMAX branded Pneumatic Shaped Solid tires will give you traction in the slipperiest applications and are the choice of Armadillo Tire, Your True Partner.

Size & Specifications

TYRE SIZE	STANDARD RIM	HEEL TYRE		DIMENSIONS(inch)		LOAD CAPACITY(LB)					
		QUICK	STANDARD	SECTION WIDTH	OVERALL DIAMETER +/-2%	FORKLIFT		OTHER VEHICLES			STATIC 0 km/h
						LOAD WHEEL 25km/h	STEER WHEEL 25km/h	6km/h	10km/h	25km/h	
5.00-8	3.00D-8	□	◆	5.1	18.0	3120	2403	3120	2833	2403	3627
18x7-8(180/70-8)△	4.33R-8	□	◆	6.0	18.0	4729	3638	4729	4288	3638	5489
6.00-9	4.00E-9	□	◆	6.1	20.5	4156	3197	4156	3770	3197	4828
6.50-10	5.00F-10	□	◆	6.5	22.4	5159	3968	5159	4685	3968	5997
7.00-12	5.00S-12	□	◆	6.9	25.6	6437	4938	6437	5831	4938	7452
8.25-15	6.50-15	□	◆	8.5	32.3	10141	7804	10141	9204	7804	11784
28x9-15(8.15-15)225/75-15	7.00-15	□	◆	8.8	27.0	8311	6393	8311	7540	6393	9656
250-15	7.00-15	□	□					Under Development			
	7.50-15	□	□					Under Development			
300-15	8.00-15	□	□					Under Development			
	7.50-20	□	□					Under Development			
10.00-20	8.00-20	□	□					Under Development			
	8.00-20	□	□					Under Development			
12.00-20	8.00-20	□	□					Under Development			
	8.00-20	□	□					Under Development			

△ The rim contour may vary from different vehicle manufacturers, please contact with EXMILE technical department for details. ◆ Available □ Under Development